



V.2025









Foshan Hongfeng Co.,Ltd

Address: No.4 Leqiang Road, Leping Sanshui,Foshan,528100,GuangDong,China Tel: 0757-88791710 ext 888 / 0592-2097262

Email: fofo@fofomedical.com Mob: +86 13055506651 www.fofomedical.com























MINI USB Compressor Nebulizer

BC68006-DC

DC Compressor Nebulizer







Device Size:

106mm*79mm*41mm

TECHNICAL FEATURES*

DC Power: 6V/2A

Medication Capacity: 8ml max.

Particle Size: 0.5 to 10µm, 5µm ≥80%

MMAD: 3.5µm

Nebulizing Head Life: ≥500hours

Sound Level: Less than 55dBA

Average Nebulization Rate: 0.2-0.3 ml/min

Operating Pressure Range: ≥16Psi

Liter Flow Range: 6-8 lpm

BC68006-DC2

DC Compressor Nebulizer



108mm*66mm*43mm

Box Size (mm)	Carton Size(mm)	PCS/CTN	
230x115x150	510x256x340	20	0.45KG

BC68006-DC1

DC Compressor Nebulizer With Li-ion Battery



106mm*100mm*52mm

Box Size (mm)			
123x115x150	510x256x320	20	0.55KG



BC68006-DC3

DC Compressor Nebulizer LED Display 10/20/30mins Setting



106mm*82mm*50mm

230x115x150	510x256x340	20	0.48KG

^{*} Datas variable depending on the medicine used. Data measured through laser diffraction technology using a physiological solution.

BC68002

Durable Compressor Nebulizer



Package Content

	Carton size(mm)	PCS/CTN	KG/CTN
170x118x275	610x175x575	10	17.8/18.6

		40HQ		Product size
ĺ	4700PCS	11200PCS	1.48KG	248/158/99

BC68002-C

Compartment Compressor Nebulizer



Package Content


Box Size (mm)	Carton Size(mm)	PCS/CTN	KG/CTN
200x110x340	570x205x640	10	18.0/18.8

20GP	40HQ		
3800PCS	9120PCS	1.5KG	289/180/107

BC68002-D

Compartment Compressor Nebulizer





BC68002 series is a high-performance compressor nebulizer with a low noise level and easy to use. The high performance compressor is suitable for continuous use and has a 2000+hours non-stop service life.

TECHNICAL FEATU**R**ES*

Input: 220V/50Hz
Power Consumption: ≤65W
Medication Capacity: 8ml
Particle Size: Respirable Fraction 0.5 to 5μm, 5μm ≥80%
MMAD: 3.5µm
Average Nebulization Rate: 0.2-0.4 ml/min
Noise Level: Below 60dB(A)
Operation Times: Non stop (hospital grade)
Compressor Pressure Range: 30-45 Psi
Operation Pressure Range: 10-14.5 Psi (0.85-1.1 bar) Liter
Flow Range: 6-8 lpm

* Datas variable depending on the medicine used. Data measured throughlaser diffraction technology using a physiological solution.

Package Content

		Carton Size(mm)	PCS/CTN	KG/CTN
[185x118x300	610x190x620	10	16.1/17.1

20GP	40HQ	Product Weight	Product Size
3960PCS	9500PCS	1.47KG	282/172/106

Gompact Nebulizers

BC6403-B

Handle Compressor Nebulizer



Package Content

		Carton Size(mm)	PCS/CTN	KG/CTN
I	175x132x270	548x180x560	8	14.5/15.5

20GP	40HQ	Product Weight	Product S
5200PCS	12480PCS	1.29KG	154/112/2

BC6403

Handle Compressor Nebulizer



Package Content

	Carton Size(mm)	PCS/CTN	KG/CTN
295x140x182	575x300x385	8	12.96/13.56

	40HQ		Product Size
3440PCS	8240PCS	1.34KG	207/170/102

BC6403-D

Handle Compressor Nebulizer



Package Content


Box Size (mm)	Carton Size(mm)	PCS/CTN	KG/CTN
217x119x258	615x232x536	10	14.1/15

20GP			
3700PCS	9000PCS	1.27KG	188/107/187

BC68001-B

BC68001-E

BC68006





Package Content

	Carton Size(mm)	PCS/CTN	KG/CTN
170x115x235	595x175x490	10	14/15

	40HQ	Product Weight	
5500PCS	13300PCS	1.28KG	155/147/105

BC68001-C

Compressor Nebulizer



Package Content

Box Size (mm)	Carton Size(mm)	PCS/CTN	KG/CTN
175x175x170	545x185x535	9	13/14

20GP	40HQ	Product Weight	Product Size
4761 PCS	11430PCS	1.32KG	172/162/98

Compressor Nebulizer



Package Content

	Carton Size(mm)	PCS/CTN	KG/CTN
175x175x170	540x180x535	9	14.1/15.1

			Product Size
4950 PCS	11880 PCS	1.58 KG	160/160/101



BC68001 series is a high-performance compressor nebulizer with a low noise level and easy to use. The high performance compressor is suitable for continuous use and has a 2000+hours non-stop service life.

TECHNICAL FEATURES*

Input: 220V/50Hz
Power Consumption: ≤65W
Medication Capacity: 8ml
Particle Size: Respirable Fraction 0.5 to 5µm, 5µm ≥80%
MMAD: 3.5μm
Average Nebulization Rate: 0.2-0.4 ml/min
Noise Level: Below 60dB(A)
Operation Times: Non stop (hospital grade)
Compressor Pressure Range: 30-45 Psi
Operation Pressure Range: 10-14.5 Psi (0.85-1.1 bar) Liter
Flow Range: 6-8 lpm

* Datas variable depending on the medicine used. Data measured throughlaser diffraction technology using a physiological solution.

Compressor Nebulizer



Package Content

	Carton size(mm)	PCS/CTN	KG/CTN
170x115x235	595x175x490	10	14/15

20GP	40HQ		
5500PCS	13300PCS	1.09KG	155/130/86

BC68005

Compressor Nebulizer



Package Content

Box size (mm)	Carton size(mm)	PCS/CTN	KG/CTN
170x115x270	595x175x565	10	14/15

4800PCS	11600PCS	1.25KG	196/160/98

Compressor Nebulizer



Package Content

Box Size (mm)	Carton Size(mm)	PCS/CTN	KG/CTN
170x115x235	595x175x490	10	13.5/14.5

5500PCS	13300 PCS	1.19KG	140/136/97



BC68006 and BC68005 are high-performance compressor nebulizer with a low noise level and easy to use. The high performance compressor is suitable for continuous use and has a 2000+ hours non-stop service life.

TECHNICAL FEATURES*

	Input: 220V/50Hz
-	Power Consumption: ≤65W
	Medication Capacity: 8ml
1	Particle Size: Respirable Fraction 0.5 to 5µm, 5µm ≥80%
ı	MMAD: 3.5µm
,	Average Nebulization Rate: 0.2-0.4 ml/min
	Noise Level: Below 60dB(A)
,	Operation Times: Non stop (hospital grade)
	Compressor Pressure Range: 30-45 Psi
,	Operation Pressure Range: 10-14.5 Psi (0.85-1.1 bar) Liter
Ī	Flow Range: 6-8 lpm

 Datas variable depending on the medicine used. Data measured throughlaser diffraction technology using a physiological solution.



BC68005-FS

Fish Compressor Nebulizer



A vivid and colourful fish moulding makes for an eye-catching nebulizer in any pharmacy. Durable and strong shell passed restric drop tests

Input: 220V/50Hz

Power Consumption: ≤65W

Medication Capacity: 8ml

Particle Size: Respirable Fraction 0.5 to 5µm, 5µm ≥80%

MMAD: 3.5µm

Average Nebulization Rate: 0.2-0.4 ml/min

Noise Level: Below 60dB(A)

Operation Times: Non stop (hospital grade)

Compressor Pressure Range: 30-45 Psi

Operation Pressure Range: 10-14.5 Psi (0.85-1.1 bar) Liter

Flow Range: 6-8 lpm

* Datas variable depending on the medicine used. Data measured through laser diffraction technology using a physiological solution.

Package Content

		PCS/CTN	KG/CTN
275x160x180	660x280x380	8	12.1/12.8

ı	3200PCS	7760PCS	1.33KG	247/132/169

BC68005-BK

Basketball Compressor Nebulizer













This nebulizer is loved by children

Give a hug to a nebulizer when atomizing, and it can relieve Children's anxiety, tension and irritability during nebulizing.

BC68005-FT Football Compressor Nebulizer













All designs can take off and become best-sellers. New creative moulds can be made by our designers at your request.

Package Content

		PCS/CTN	KG/CTN		40HQ
200x200x200	615x205x630	9	13.5/14.5	3231PCS	7758PCS









BC68005-BR1

BC68005-PG

Bear Compressor Nebulizer



Piggy Compressor Nebulizer



BC68005-TG

BC68005-PB

BC68005-PD

Tiger Compressor Nebulizer



Polar Bear Compressor Nebulizer



















Various design options, such as the ones seen above, and others available to request (animals like tigers, koalas, kittens).

Package Content

Box Si		Carton Size(mm)	PCS/CTN	KG/CTN
180x1	53x265	630x185x555	8	14.4/15

20GP	40HQ		Product Size
3520PCS	8480PCS	1.36KG	166/140/213

Input: 220V/50Hz	1
Power Consumption: ≤65W	
Medication Capacity: 8ml	
Particle Size: Respirable Fraction 0.5 to 5µm, 5µm ≥80%	
MMAD: 3.5µm	
Average Nebulization Rate: 0.2-0.4 ml/min	
Noise Level: Below 60dB(A)	
Operation Times: Non stop (hospital grade)	
Compressor Pressure Range: 30-45 Psi	
Operation Pressure Range: 10-14.5 Psi (0.85-1.1 bar) Liter	
Flow Range: 6-8 lpm	

^{*} Datas variable depending on the medicine used. Data measured through laser diffraction technology using a physiological solution.

BC68005-DG

Dog Compressor Nebulizer



Package Content

		n Size(mm) PCS/CTN	
220X140X230	450X290X460 8		15.04/15.64
20GP			Product Size
3600PCS	8640PCS	1.42KG	205/127/213

BC68005-BR2

Bear Head Nebulizer



Package Content

		PCS/CTN	KG/CTN
205X135X250	560X215X525	8	14.4/15
3600PCS	8640PCS	1.42KG	186/125/18

BC68005-CAT

Cat Compressor Nebulizer



Package Content

I	Box Size (mm)	Carton Size(mm)	PCS/CTN	KG/CTN
	240X150X260	505X475X545	12	20.4/25
I				,
	20GP			Product Size
	5256PCS	12600PCS	1.42KG	220/140/230

BC68005-QQ

Penguin Compressor Nebulizer












Kids Use Low Noise

Cute designs for pediatric nebulizers. We have many Innovative moulds ODM/OEM welcome
The Penguin design is compact and portable, very popular in the American and European markets.

One of Amazon's hot sale items. Carry bag is optional.

Nebulizer Kits

Highly Effective Nebulizer Cup



Kit A



		PCS/CTN	KG/CTN
35500/86000	580x380x360	100	10.0/11.0

Kit B



		PCS/CTN	KG/CTN
26000/62200	600x400x380	100	10.0/11.7

Dual Function Compressor Nebulizer

Nebulizer/Suction/Nasal Aspirator







Compressor Nebulizer/Suction

Highly Effective Nebulizer Motor with 3 Bearings

SPECIFICATIONS

- Rated Current : ≤0.7A (when load)- Rated Power : ≤80W (when load)

- NO-load Air Flow : ≥ 8 L/min

- Load Air Flow : when 0.1 MPa (14.5 PSI) \geq 5L/min

- Max Pressure : 35 PSI - Noise : ≤60 dB




Compressor Motor







Package content

Qty/Pallet	Pallet Size(mm)	N.W./G.W.
704pcs	1030X990X1030	630/650Kg
20GP	40HQ	Product weight
18240PCS	28160PCS	0.88KG







Suction Machine With Battery

WITH RECHARGEABLE BATTERY, ANTI RUSTING STRONG STEEL LOW NOISE AND LONG LIFE



Oil Free



Suction Bottom
Hidden Inside



Low Noise



Requiated Negati

SPECIFICATIONS

- · Power Supply:
- AC 100V-240V, 50HZ/60HZ; DC 12V 2A
- Input Power: 30VA \pm 25%
- · Max Negative Pressure Value: ≥ 0.075MPa
- Negative Pressure Adjustment Range: from 0.02 MPa to 0.075 MPa
- · Free Air Flow Rate : ≥ 15L / min
- · Pumping Rate: ≥ 7L/min
- · Jug Volume: 1000ml
- · Noise Level: ≤ 60dBa
- · Battery (for DC): 2600mA
- · Unit Weight: 1.8KG
- · Optionally Equiped with Car Charger



Phiegm Suction Machine

FO9001-A



Accessories






FO9001-B

Portable Suction Machine



FO9001-C









SPECIFICATIONS

- Rated Voltage: AC220V \pm 10% / 50Hz \pm 2%

- Input Power : ≤90W

- Noise : 65 dB(A)

- Max Negative Pressure Value : ≥ 0.075MPa

- Pumping Rate : 15L/min - Jug Volume : 1000 ml

- Continuous Working Time : within 30 min

- Rest Intervals : \ge 30 min

- Portable Design

Package content

						40HQ
Α	360x190x270	395x372x565	4	14.3/15.1	1360PCS	3300PCS
В	385x205x300	425x397x620	4	14.5/15.5	1080PCS	2600PCS
С	330x245x260	510x350x545	4	16.5/17.5	1170PCS	2820PCS
D	390x390x530	620x420x645	4	15.0	1400PCS	3400PCS