

# Stars CL261 Cabinet ESS



## Small Size, Big Power.

\*Upgrade to Pro for optional MPPT, STS, and EV charging

\*Optional Protective Top Cover

High Efficiency  
Ultra-Safe  
Plug & Play  
Smart Integration

### Ideal for

- Commercial Peak Shaving
- Virtual Power Plant (VPP) Integration
- Critical Backup Power
- Three-Phase Load Balancing



## Why Choose Stars CL261?

### High Efficiency & Savings

- 261 kWh capacity, 90% RTE efficiency
- 125 kW fast response charge/discharge
- Wide DC voltage range: 728~936 V

### Durable & Modular

- Plug & play — no civil works
- 8,000+ cycles for long life
- Reliable in extreme temps (-35°C to 55°C)

### Safety & Reliability

- IP55-rated enclosure with liquid cooling
- Automatic coolant replenishment
- Multi-layer safety: thermal runaway, fire protection, aerosol suppression, real-time alerts

### Smart Integration

- All-in-one system with battery, BMS, AC-DC converter, thermal & fire protection
- Supports Modbus, IEC104, MQTT for easy integration

#### Telephone

+86-731 **8256 6160** (CHN) / +65 **9622 5139** (SGP) / +1 (0) **949 678 2338** (USA)

ADD:

**CHN** - 38th Floor, North Tower, Jinmao Plaza, Yuelu District, Changsha City, Hunan Province, China

**SGP** - No.79 Lentor Street, Singapore 786789

**USA** - 5900 Balcones Drive Suite 100 Austin TX, 78731 USA

**ITA** - Via Messina 17, 20154 - Milano (MI) - IT

#### WhatsApp

+86 **181 7589 6293**

<https://www.wenergystorage.com>

E-mail: [export@wenergypro.com](mailto:export@wenergypro.com)

# Stars CL261 Cabinet ESS



Small Size, Big Power.

## Product Parameters

Category	Parameter	Specification
System Parameters	Rated Energy	261kWh
	Maximum Energy Efficiency	≥90%
	Operating Temperature	-35°C ~ 55°C (Derated above 45°C)
	Operating Humidity	0%~95% RH (non-condensing)
	Depth of Discharge (DOD)	100%
	Auxiliary Power Supply	Self-powered/External-powered
	Noise Level	≤75dB
	Maximum Cycle Life	≥ 8,000 Cycles @ 100% DoD, EoL 70% SoH
	Maximum Operating Altitude	4000m (Derated above 2000m)
	Thermal Management	Intelligent Liquid Cooling (with Automatic Refill)
	Safety Features	Pack/Module Aerosol + Module Water Mist + Top Vent + Active Alert
	Protection Rating	IP55
	Communication Interface	LAN/RS485
	Communication Protocol	Modbus/IEC104/MQTT
	Wiring Method	Three-phase four-wire
Connection Type	On-Grid /Off Grid	
Standards & Certifications	IEC/EN 62619, IEC 60730-1, IEC 62477, IEC 60529, IEC 61000-6-2, IEC 61000-6-4	
AC Parameters	Rated Charge/Discharge Power	125kW
	Rated Voltage	400V (-15%~+15%)
	Rated Grid Frequency	50Hz
	Power Factor	-1~1
DC Parameters	Cell Type	LFP 3.2V/314Ah
	DC Voltage Operating Range	728~936V
	DC Protection	Contactora + FUSE
Mechanical Parameters	Cabinet Dimensions (W×D×H)	(1012±10) * (1380±10) * (2270±10) mm
	Weight	≤2500kg
	Installation Method	Floor-mounted

### Telephone

+86-731 **8256 6160** (CHN) / +65 **9622 5139** (SGP) / +1 (0) **949 678 2338** (USA)

### WhatsApp

+86 **181 7589 6293**

ADD:

**CHN** - 38th Floor, North Tower, Jinmao Plaza, Yuelu District, Changsha City, Hunan Province, China

**SGP** - No.79 Lentor Street, Singapore 786789

**USA** - 5900 Balcones Drive Suite 100 Austin TX, 78731 USA

**ITA** - Via Messina 17, 20154 - Milano (MI) - IT

<https://www.wenergystorage.com>

E-mail: [export@wenergypro.com](mailto:export@wenergypro.com)